

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Lampefeber, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 805-001

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	16	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 733
On-mode power (P_{on}), expressed in W	16,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control	Height	450	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	450	
	Depth	3	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,452 0,401
Parameters for LED and OLED light sources:			
R9 colour rendering index value	64	Survival factor	0,90
the lumen maintenance factor	0,96		

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report

Sample : Downlight Date : 2021-08-26 10:09:06
Specification : LUCIA 350-C-18W-927 Sam. Status :
Sample No. : RP-210398-10 Instrument : HAAS-2000(EVERFINE)
Manufacturer : V Test by : hanyu YI

Test Condition

Temperature : 25.3Deg RH : 65.0%
WL Range : 380nm-780nm IP : 53193 (81%)
Test Mode : Fast Test T : 122 ms
Sensitivity : High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4527$ $y = 0.4019$ / $u' = 0.2618$ $v' = 0.5229$ ($duv = -2.65e-03$)

CCT= 2733K Prcp WL: Ld=585.0nm Purity=56.5%

Peak WL: Lp=626nm FWHM: =136.1nm Ratio:R=26.7% G=70.1% B=3.2%

Render Index: Ra = 92.3

R1 =96 R2 =98 R3 =94 R4 =92 R5 =96 R6 =93 R7 =88

R8 =81 R9 =64 R10=97 R11=95 R12=82 R13=98 R14=97 R15=91

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters


Flux = 2364.3 lm Eff. : 144.69 lm/W Fe = 8.4221 W

Electrical parameters

V = 32.68 V I = 0.5000 A P = 16.34 W PF = 1.000 F=0.00 Hz

E-LITE LIGHTING Co.,Ltd.

Model placed on the Union market from 08/02/2021



EPREL registration number: 1110830

<https://eprel.ec.europa.eu/qr/1110830>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Lampefeber

Website:

Email: mail@lampefeber.com

Phone: 86361722

Address:

Lilleringvej 30
8462 Harlev
Denmark