

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 818-001

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	11	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	592 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2600...3800
On-mode power (P_{on}), expressed in W	12,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,99
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,00	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	60	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	1 300	
	Depth	37	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,458 0,410
Parameters for directional light sources:			
Peak luminous intensity (cd)	1 031	Beam angle in degrees, or the range of beam angles that can be set	45
Parameters for LED and OLED light sources:			
R9 colour rendering index value	67	Survival factor	0,98
the lumen maintenance factor	0,97		

(a) : not applicable;

(b) : not applicable;

Spectrum Test Report

Sample :
 Specification : LZ-1147 3000k
 Sample No. : 2
 Manufacturer :


Date : 2024-04-17
 Sam. Status :
 Instrument : HaasSuite(EVERFINE)
 Test by : XIAOXIN
 Assessor : damin

Test Condition

Temperature : 25.3Deg
 WL Range : 380nm-780nm
 Test Mode : Fast Test

RH : 65.0%
 IP : 52767 (81%)
 T : 272 ms
 Sensitivity : High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4622$ $y = 0.4069$ / $u' = 0.2657$ $v' = 0.5263$ ($duv = -1.56e-03$)
 CCT= 2639K Prcp WL: Ld=585.0nm Purity=60.9%
 Peak WL: Lp=607nm FWHM: =104.7nm Ratio:R=25.9% G=71.8% B=2.3%

Render Index: Ra = 82.4

R1 =82 R2 =93 R3 =93 R4 =80 R5 =83 R6 =94 R7 =79
 R8 =55 R9 =5 R10=86 R11=81 R12=81 R13=85 R14=97 R15=73
 LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 472.60 lm Eff. : 39.59 lm/W Fe = 1.4514 W


Electrical parameters

V = 229.9 V I = 0.06790 A P = 11.94 W PF = 0.7646 F=49.99 Hz

EVERFINE CORPORATION

<http://www.everfine.cn>

Model placed on the Union market from 05/01/2024



EPREL registration number: 2018583

<https://eprel.ec.europa.eu/qr/2018583>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark