

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 825-001

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	CLS		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	Yes	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	484 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	12,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,00	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, lighting control	Height	190	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	35	
	Depth	35	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,459 0,413
Parameters for LED and OLED light sources:			
R9 colour rendering index value	60	Survival factor	0,96
the lumen maintenance factor	0,90		

(a) : not applicable;

(b) : not applicable;

Lightsource Test Report


Product Information

Product Category: UFO SP1
Product Number: 176

Product Type: UFO SP1 可称球 S
Submitted Unit: MERLONG

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.4638$ $y=0.4118$ $u(u')=0.2645$ $v=0.3523$ $v'=0.5284$
 CCT: $T_c=2654K$ ($duv=0.00011$) Color Ratio: $R=0.267$ $G=0.711$ $B=0.022$
 Peak Wavelength: 633.1nm Half Bandwidth: 143.5nm
 Dominant Wavelength: 584.4nm Color Purity: 0.628
 CRI: $Ra=92.0$ TM30: $Rf=92$ $Rg=100$
 R1 =92 R2 =96 R3 =98 R4 =93 R5 =92 R6 =96 R7 =90 R8 =79
 R9 =54 R10=90 R11=94 R12=86 R13=93 R14=98 R15=87
 Color Quality Scales: $Qa=90.0$ $Qb=92.3$ $Qc=92.7$ $Qd=95.3$
 Q1 =86 Q2 =55 Q3 =90 Q4 =90 Q5 =91 Q6 =91 Q7 =90 Q8 =91
 Q9 =96 Q10=93 Q11=93 Q12=92 Q13=91 Q14=85 Q15=85



Photometric Parameters

Luminous Flux: 484.20 lm Efficiency: 33.21 lm/W Radiant Power: 1.706 W
 EEF: 0.34 Energy Efficiency Class: B (EU 874-2012)

Electric Parameters

Voltage: 220.00V Current: 0.0770A Power: 14.58W
 Power Factor: 0.8640 Frequency: 49.99Hz


Test Information

Scan Range: 380-800:1nm Photometric Method: sphere-spectroradiometer
 Stabilization Time: 0 Sec Photometric Condition: Sphere diameter: 1.50m, 411
 Max of Signal: 43875 (3394) CCD Integration Time: 349.31 ms

Condition: Tx:29.6°C, Tl:28.9°C, R.H.:60%
 Test Lab:
 Operator: yg

Test Device: Inventime CMS-2S (Plus)
 Test Time: 2022-08-10 15:53:44
 Inspector:

Model placed on the Union market from 01/02/2023



EPREL registration number: 1526782

<https://eprel.ec.europa.eu/qr/1526782>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark