

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LOOM Design

**Supplier's address:** Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

**Model identifier:** 826-001

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	CLS		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	Yes	Dimmable:	Yes

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	16	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	511 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power ( $P_{on}$ ), expressed in W	16,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0,00	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer dimensions without separate control gear, lighting control	Height	1 900	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	350	
	Depth	350	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,459 0,413
<b>Parameters for directional light sources:</b>			
Peak luminous intensity (cd)	191	Beam angle in degrees, or the range of beam angles that can be set	36
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	60	Survival factor	0,96
the lumen maintenance factor	0,90		

(a) : not applicable;

(b) : not applicable;

**Lightsources Test Report**

**Product Information**

Product Category: UFO SP1  
Product Number: 162

Product Type: UFO SP1 可移球  
Submitted Unit: MERLONG

**CIE Colorimetric Parameters**

Chromaticity coordinates:  $x=0.4593$   $y=0.4130$   $u(u')=0.2611$   $v=0.3521$   $v'=0.5282$   
 CCT:  $T_c=2727K$  ( $duv=0.00092$ ) Color Ratio:  $R=0.261$   $G=0.715$   $B=0.024$   
 Peak Wavelength: 435.7nm Half Bandwidth: 148.5nm  
 Dominant Wavelength: 583.8nm Color Purity: 0.618  
 CRI:  $R_a=93.0$  TM30:  $R_f=92$   $R_g=99$   
 R1 =93 R2 =96 R3 =99 R4 =94 R5 =93 R6 =96 R7 =92 R8 =82  
 R9 =60 R10=91 R11=95 R12=84 R13=94 R14=98 R15=89  
 Color Quality Scales:  $Q_m=91.5$   $Q_f=93.7$   $Q_g=93.2$   $Q_h=94.7$   
 Q1 =89 Q2 =95 Q3 =91 Q4 =90 Q5 =92 Q6 =93 Q7 =93 Q8 =93  
 Q9 =97 Q10=95 Q11=94 Q12=93 Q13=93 Q14=87 Q15=88



**Photometric Parameters**

Luminous Flux: 511.57 lm Efficiency: 25.72 lm/W Radiant Power: 1.800 W  
 EEF: 0.44 Energy Efficiency Class: B (EU 874-2012)

**Electric Parameters**


Voltage: 220.00V Current: 0.0990A Power: 19.89W  
 Power Factor: 0.9170 Frequency: 50.00Hz

**Test Information**

Scan Range: 380-800:1nm Photometric Method: sphere-spectroradiometer  
 Stabilization Time: 0 Sec Photometric Condition: Sphere diameter: 1.50m, 411  
 Max of Signal: 52065 (3701) CCD Integration Time: 409.49 ms

Condition: Tx:31.5°C, Tl:30.3°C, R.H.:60% Test Device: Inventime CMS-2S (Plus)  
 Test Lab: Test Time: 2022-07-27 11:45:47  
 Operator: yg Inspector:

Model placed on the Union market from 01/02/2023



**EPREL registration number:** 1526835

<https://eprel.ec.europa.eu/qr/1526835>

**Supplier:** Lampefeber A/S (Importer)

**Website:** [www.lampefeber.com](http://www.lampefeber.com)

**Customer care service:**

**Name:** Main Office

**Website:** [www.loom-design.com](http://www.loom-design.com)

**Email:** [mail@lampefeber.com](mailto:mail@lampefeber.com)

**Phone:** +4586361722

**Address:**

Lilleringvej 30  
8462 Harlev  
Denmark