

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 873-004

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:


Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	60	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	3 060 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	60,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	55	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	360	
	Depth	360	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,458 0,410
Parameters for LED and OLED light sources:			
R9 colour rendering index value	61	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a): not applicable;

(b): not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4655$ $y=0.4149$ / $u'=0.2642$ $v'=0.5298$
 CCT=2656K (Duv=0.0011) Dominant WL:Ld =584.1nm Purity=64.3%
 Ratio:R=26.9% G=70.7% B=2.4% Peak WL:Lp=625.9nm FWHM=141.2nm
 Render Index:Ra=93.9
 R1 =94 R2 =97 R3 =100 R4 =94 R5 =94 R6 =98 R7 =92
 R8 =82 R9 =61 R10=93 R11=97 R12=87 R13=95 R14=99 R15=89

Photo Parameters:

Flux = 3058 lm Eff. : 57.11 lm/W Fe = 10.83 W

Electrical parameters:


V = 249.82 V I = 0.2221 A P = 53.55 W PF = 0.9652

Status: Integral T = 85 ms Ip = 33099 (51%)

Model:SAV360A60OFA222-A1
 Tester:彭金英
 Temperature:25.3Deg
 Manufacturer:SAT

Number:SAV360A60OFA222-A1
 Date:2025-01-20 17:28:12
 Humidity:51%
 Remarks:

Model placed on the Union market from 21/02/2025



EPREL registration number: 2271455

<https://eprel.ec.europa.eu/qr/2271455>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark