

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 885-001

Type of light source:

| | | | |
|---|------|---------------------------------|----------------------------|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | LED | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |

Product parameters

| Parameter | Value | Parameter | Value |
|--|----------------------|--|---|
| General product parameters: | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 4 | Energy efficiency class | C |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 700 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 567 |
| On-mode power (P_{on}), expressed in W | 4,0 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 90 |
| Outer dimensions without separate control gear, light- | Height | 128 | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
| | Width | 128 | |
| | Depth | 35 | |
| | | | See image in last page |

| | | | |
|---|------|------------------------------------|----------------|
| ing control parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,467 0,406 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 52 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,96 | | |

(a) : not applicable;


(b) : not applicable;

| | | | |
|--|------|---------------------------------|------|
| Supplier's name or trade mark: | | | |
| Supplier's address: | | | |
| Model Identifier: OTTO-5W-2835-4P5SX2 | | | |
| Type of light source: COB LED | | | |
| Lighting Technology Used : | LED | Non-directional or directional: | NDLS |
| Mains or non-mains: | NMLS | Connected light source (CLS): | NO |
| Colour-tunable light source: | NO | Envelope: | NO |
| High luminance light source: | NO | | |
| Anti-glare shield: | NO | Dimmable: | YES |

Product parameters:

| Parameter | Value (from data sheet) | Parameter | Value (from data sheet) |
|-----------|-------------------------|-----------|-------------------------|
|-----------|-------------------------|-----------|-------------------------|

General product parameters:

| | | | |
|--|---|--|---|
| Energy consumption in onmode (kWh/1000h) | 4 | Energy efficiency class | C |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 700 in a sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2567K |
| On-mode power (p_{on}), expressed in W | 4 | Standby power (p_{sb}), expressed in W and rounded to the second decimal | not applicable |
| Networked standby power (p_{net}) for CLS, expressed in w and rounded to the second decimal | not applicable | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 90 |
| Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Height: <u> 128 </u> Width: <u> 128 </u> Depth: <u> 35 </u> | Spectral power distribution in the range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | x 0,4669 - y 0,4058 |

Parameters for directional light sources:

| | | | |
|------------------------------|---|--|---|
| Peak luminous intensity (cd) | - | Beam angle in degrees, or the range of beam angles that can be set | - |
|------------------------------|---|--|---|

Parameters for LED and OLED light sources:

| | | | |
|---------------------------------|------|-----------------|-----|
| R9 colour rendering index value | 52 | Survival factor | 0,9 |
| the lumen maintenance factor | 0,96 | | |

Parameters for LED and OLED mains light sources:

| | | | |
|---|---------|---------------------------------------|-----|
| displacement factor ($\cos \phi 1$) | x,xx | Colour consistency in McAdam ellipses | x |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | (yes/-) | If yes then replacement claim (W) | x |
| Flicker metric (Pst LM) | x,x | Stroboscopic effect metric (SVM) | x,x |

EPREL registration number: 2691057

Model placed on the Union market from 09/04/2026.



<https://eprel.ec.europa.eu/qr/2691057>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark