

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LOOM Design

Supplier's address: Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

Model identifier: 885-002

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	C
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 567
On-mode power (P_{on}), expressed in W	4,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,467 0,406	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	52	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a) '-': not applicable;


(b) '-': not applicable;

Supplier's name or trade mark:			
Supplier's address:			
Model Identifier: OTTO-5W-2835-4P5SX2			
Type of light source: COB LED			
Lighting Technology Used :	LED	Non-directional or directional:	NDLS
Mains or non-mains:	NMLS	Connected light source (CLS):	NO
Colour-tunable light source:	NO	Envelope:	NO
High luminance light source:	NO		
Anti-glare shield:	NO	Dimmable:	YES

Product parameters:

Parameter	Value (from data sheet)	Parameter	Value (from data sheet)
-----------	-------------------------	-----------	-------------------------

General product parameters:

Energy consumption in onmode (kWh/1000h)	4	Energy efficiency class	C
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	700 in a sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2567K
On-mode power (p_{on}), expressed in W	4	Standby power (p_{sb}), expressed in W and rounded to the second decimal	not applicable
Networked standby power (p_{net}) for CLS, expressed in W and rounded to the second decimal	not applicable	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height: <u>128</u> Width: <u>128</u> Depth: <u>35</u>	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
Claim of equivalent power	-	If yes, equivalent power (W)	
		Chromaticity coordinates (x and y)	x 0,4669 - y 0,4058

Parameters for directional light sources:

Peak luminous intensity (cd)	-	Beam angle in degrees, or the range of beam angles that can be set	-
------------------------------	---	--	---

Parameters for LED and OLED light sources:

R9 colour rendering index value	52	Survival factor	0,9
the lumen maintenance factor	0,96		

Parameters for LED and OLED mains light sources:

displacement factor ($\cos \phi 1$)	x,xx	Colour consistency in McAdam ellipses	x
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	(yes/-)	If yes then replacement claim (W)	x
Flicker metric (Pst LM)	x,x	Stroboscopic effect metric (SVM)	x,x

EPREL registration number: 2803033

Model placed on the Union market from 27/07/2026.



<https://eprel.ec.europa.eu/qr/2803033>

Supplier: Lampefeber A/S (Importer)

Website: www.lampefeber.com

Customer care service:

Name: Main Office

Website: www.loom-design.com

Email: mail@lampefeber.com

Phone: +4586361722

Address:

Lilleringvej 30
8462 Harlev
Denmark