

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LOOM Design

**Supplier's address:** Main Office, Lilleringvej 30, 8462 Aarhus Harlev, DK

**Model identifier:** 886-003

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

## Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

### General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	C
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 567
On-mode power ( $P_{on}$ ), expressed in W	4,0	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	128	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	128	
	Depth	35	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,467 0,406
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	52	Survival factor	0,90
the lumen maintenance factor	0,96		

(a) : not applicable;


(b) : not applicable;

<b>Supplier's name or trade mark:</b>			
<b>Supplier's address:</b>			
<b>Model Identifier:</b> OTTO-5W-2835-4P5SX2			
<b>Type of light source:</b> COB LED			
Lighting Technology Used :	LED	Non-directional or directional:	NDLS
Mains or non-mains:	NMLS	Connected light source (CLS):	NO
Colour-tunable light source:	NO	Envelope:	NO
High luminance light source:	NO		
Anti-glare shield:	NO	Dimmable:	YES

**Product parameters:**

Parameter	Value (from data sheet)	Parameter	Value (from data sheet)
-----------	-------------------------	-----------	-------------------------

**General product parameters:**

Energy consumption in onmode (kWh/1000h)	4	Energy efficiency class	C
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	700 in a sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2567K
On-mode power ( $p_{on}$ ), expressed in W	4	Standby power ( $p_{sb}$ ), expressed in W and rounded to the second decimal	not applicable
Networked standby power ( $p_{net}$ ) for CLS, expressed in w and rounded to the second decimal	not applicable	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height: <u>  128  </u> Width: <u>  128  </u> Depth: <u>  35  </u>	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
Claim of equivalent power	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	x 0,4669 - y 0,4058

**Parameters for directional light sources:**

Peak luminous intensity (cd)	-	Beam angle in degrees, or the range of beam angles that can be set	-
------------------------------	---	--	---

**Parameters for LED and OLED light sources:**


R9 colour rendering index value	52	Survival factor	0,9
the lumen maintenance factor	0,96		

**Parameters for LED and OLED mains light sources:**

displacement factor ( $\cos \phi 1$ )	x,xx	Colour consistency in McAdam ellipses	x
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	(yes/-)	If yes then replacement claim (W)	x
Flicker metric (Pst LM)	x,x	Stroboscopic effect metric (SVM)	x,x

EPREL registration number: 2692685

Model placed on the Union market from 10/04/2026.



<https://eprel.ec.europa.eu/qr/2692685>

**Supplier:** Lampefeber A/S (Importer)

**Website:** [www.lampefeber.com](http://www.lampefeber.com)

**Customer care service:**

**Name:** Main Office

**Website:** [www.loom-design.com](http://www.loom-design.com)

**Email:** [mail@lampefeber.com](mailto:mail@lampefeber.com)

**Phone:** +4586361722

**Address:**

Lilleringvej 30  
8462 Harlev  
Denmark